

Overview

HPE OfficeConnect 1620 Switch Series



Models

| | |
|-----------------------------------|--------|
| HPE OfficeConnect 1620 8G Switch | JG912A |
| HPE OfficeConnect 1620 24G Switch | JG913A |
| HPE OfficeConnect 1620 48G Switch | JG914A |

Key features

- Entry-level, smart managed layer 2 switches
- 8-, 24-, and 48-port gigabit models are rack mount capable with included hardware
- 8- and 24 port models run quiet (fanless)
- All models include internal power supplies
- Limited Lifetime Warranty

Product overview

HPE OfficeConnect 1620 Switch Series are entry configurable switches for small business networking, a step up from unmanaged devices, with features to enhance network security, performance and reliability. The series is part of the OfficeConnect portfolio of Hewlett Packard Enterprise small business networking products.

These Gigabit switches are plug-and-play out of the box, yet network operations can be fine-tuned through features available from a simple Web browser-based GUI, if necessary. Enhance security using virtual LANs, link aggregation, or IGMP Snooping boost uplink performance, and loop prevention enhances network reliability..

Overview

The series consists of 8-, 24-, and 48-port 10/100/1000BASE-T models each providing non-blocking gigabit per port performance. All models can be rack mounted and include the necessary rack-mounting hardware; the 8-port model can also be wall mounted. All models come with internal power supplies and localized power cord removing the need to manage external power adapters. The 8- and 24-port models are fanless for silent operation.

This series comes with a Limited Lifetime Warranty providing advance hardware replacement with next business day shipment in most countries, 24x7 phone support available for the first 90 days, and electronic and business hours phone support for the entire warranty period.

Features and benefits

Management

- **Simple Web management**
allows for easy management of the switch even by nontechnical users through an intuitive Web GUI; supports HTTP and HTTP Secure (HTTPS)
- **Secure Web GUI**
provides a secure, easy-to-use graphical interface for configuring the switch via HTTPS.
- **SNMPv1, v2c, v3**
facilitates management of the switch, as the device can be discovered and monitored from an SNMP management station.
- **Port mirroring**
enables traffic on a port to be simultaneously sent to a network analyzer for monitoring.
- **Default DHCP client mode**
allows the switch to be directly connected to a network, enabling plug-and-play operation; in absence of a DHCP server on the network, the switch will fall back to a unique static address determined by the switch's MAC address.
- **Network Time Protocol (NTP)**
synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time.
- **Manual network time configuration**
manually set the date and time on the switch in the absence of a NTP server.
- **Dual flash images**
provides independent primary and secondary operating system files for backup while upgrading
- **Limited CLI**
enables users to quickly deploy and troubleshoot devices in the network.

Quality of Service (QoS)

- **IEEE 802.1p prioritization with DSCP**
delivers data from the switch to devices based on the priority and type of traffic using Differentiated Services Code Point (DSCP).
- **Broadcast control**
allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic.
- **Rate limiting**
sets per-port ingress enforced maximums and per-port, per-queue minimums.

Connectivity

- **Auto-MDI/MDIX**
automatically adjusts for straight-through or crossover cables on all ports.

Overview

- **IEEE 802.3X flow control**
provides a flow throttling mechanism propagated through the network to prevent packet loss at a congested node.
- **Loopback detection**
if the switch detects a loop, it disables the source port from forwarding data packets originating from the switch to avoid broadcast storms.
- **Energy Efficient Ethernet**
compliant with IEEE 802.3az standard requirements to save energy during periods of low data activity.
- **Port power save mode**
enables a port to operate at the lowest transmission speed or go down during a specific time range on certain days of a week. The port resumes when the effective time period ends.
- **Cable test**
performs a check on the status of the cable connected to an Ethernet port on the device. The test determines whether a short circuit or open circuit is present on the cable and the approximate length to the fault in the cable.

Performance

- **Half-/full-duplex auto-negotiating capability on every port**
doubles the throughput of every port.
- **IGMP snooping, v1, v2 and v3**
improves network performance through multicast filtering, instead of flooding traffic to all ports.

Layer 2 switching

- **VLAN support and tagging**
supports IEEE 802.1Q with 4096 simultaneous VLAN IDs.
- **Jumbo frame support**
supports up to 10 kilobyte frame size to improve the performance of large data transfers.

Resiliency and high availability

- **Link aggregation**
groups together multiple ports (up to a maximum of eight ports per trunk) automatically using Link Aggregation Control Protocol (LACP), or manually, to form an ultra-high-bandwidth connection to the network backbone; helps prevent traffic bottlenecks. **NOTE:** 8 port model support 4 trunks, 24 port model support 8 trunks, and the 48 port model support 16 trunks.

Warranty and support

- **Limited Lifetime Warranty**
this series comes with a Limited Lifetime Warranty providing advance hardware replacement with next business day shipment in most countries, 24x7 phone support available for the first 90 days, and electronic and business hours phone support for the entire warranty period. See <http://www.hpe.com/networking/warrantysummary> for full warranty and support information included with your product purchase.

Configuration

Build To Order: BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

| | |
|--|------------------------------------|
| HPE OfficeConnect 1620 8G Switch | JG912A |
| <ul style="list-style-type: none"> 8 RJ-45 autosensing 10/100/1000 ports 1U - Height | See Configuration NOTE:1 |
| PDU Cable NA/MEX/TW/JP | JG912A#B2B |
| <ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) | |
| PDU Cable NA/MEX/TW/JP | JG912A#B2C |
| <ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) | |
| High Volt Switch/Router to Wall Power Cord | JG912A#B2E |
| <ul style="list-style-type: none"> NEMA L6-20P Cord (NA/MEX/JP/TW) | |
| HPE OfficeConnect 1620 24G Switch | JG913A |
| <ul style="list-style-type: none"> 24 RJ-45 autosensing 10/100/1000 ports 1U - Height | See Configuration NOTE:1 |
| PDU Cable NA/MEX/TW/JP | JG913A#B2B |
| <ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) | |
| PDU Cable NA/MEX/TW/JP | JG913A#B2C |
| <ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) | |
| High Volt Switch/Router to Wall Power Cord | JG913A#B2E |
| <ul style="list-style-type: none"> NEMA L6-20P Cord (NA/MEX/JP/TW) | |
| HPE OfficeConnect 1620 48G Switch | JG914A |
| <ul style="list-style-type: none"> 48 RJ-45 autosensing 10/100/1000 ports 1U - Height (Desktop Model?) | See Configuration NOTE:1 |
| PDU Cable NA/MEX/TW/JP | JG914A#B2B |
| <ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) | |
| PDU Cable NA/MEX/TW/JP | JG914A#B2C |
| <ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) | |
| High Volt Switch/Router to Wall Power Cord | JG914A#B2E |
| <ul style="list-style-type: none"> NEMA L6-20P Cord (NA/MEX/JP/TW) | |

Configuration Rules:

Configuration

Note 1 Localization (Wall Power Cord) required on orders without #B2B, #B2C (PDU Power Cord) or #B2E.
(See Localization Menu)

Internal Power Supplies

Power supplies included

Remarks Drop down under power supply should offer the following options and results:
Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan
or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)
Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box
Level CTO)
High Volt Switch/Router/Power Supply to Wall Power Cord - #B2E Option. (Offered only in North
America, Mexico, Taiwan, and Japan)

Technical Specifications

HPE OfficeConnect 1620 8G Switch (JG912A)

| | | |
|-----------------------------------|--|---|
| I/O ports and slots | 8 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only | |
| Additional ports and slots | 1 RJ-45 console port to access limited CLI port | |
| Physical characteristics | Dimensions | 10.47(w) x 6.38(d) x 1.73(h) in (26.59 x 16.21 x 4.39 cm) (1U height) |
| | Weight | 2.2 lb (1 kg) |
| Memory and processor | MIPS @ 500 MHz, 32 MB flash, 128 MB SDRAM; packet buffer size: 512 KB | |
| Mounting and enclosure | Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included), wall mount | |
| Performance | 100 Mb Latency | < 7 μ s |
| | 1000 Mb Latency | < 5 μ s |
| | Throughput | up to 11.9 Mpps (64-byte packets) |
| | Switching capacity | 16 Gbps |
| | MAC address table size | 8192 entries |
| Reliability | MTBF (years) | 138.89 |
| Environment | Operating temperature | 32°F to 104°F (0°C to 40°C) |
| | Operating relative humidity | 5% to 95%, noncondensing |
| | Nonoperating/Storage temperature | -40°F to 158°F (-40°C to 70°C) |
| | Nonoperating/Storage relative humidity | 5% to 95%, noncondensing |
| | Altitude | up to 16,404 ft (5 km) |
| | Acoustic | No Fan |
| Electrical characteristics | Frequency | 50/60 Hz |
| | Voltage | 100 - 240 VAC, rated |
| | Maximum power rating | 7 W |
| | Notes | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| Safety | IEC 60950-1; EN 60950-1; CSA 22.2 60950-1; UL 60950-1 2nd Edition | |
| Emissions | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A | |
| Services | Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. | |

HPE OfficeConnect 1620 24G Switch (JG913A)

| | |
|----------------------------|--|
| I/O ports and slots | 24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, |
|----------------------------|--|

Technical Specifications

| | |
|---|--|
| | IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |
| Additional ports and slots | 1 RJ-45 console port to access limited CLI port |
| Physical characteristics | |
| Dimensions | 17.32(w) x 6.81(d) x 1.73(h) in (43.99 x 17.3 x 4.39 cm) (1U height) |
| Weight | 4.85 lb (2.2 kg) |
| Memory and processor | MIPS @ 500 MHz, 32 MB flash, 128 MB SDRAM; packet buffer size: 512 KB |
| Mounting and enclosure | Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included) |
| Performance | |
| 100 Mb Latency | < 7 μ s |
| 1000 Mb Latency | < 5 μ s |
| Throughput | up to 35.7 Mpps (64-byte packets) |
| Switching capacity | 48 Gbps |
| MAC address table size | 8192 entries |
| Reliability | |
| MTBF (years) | 123.46 |
| Environment | |
| Operating temperature | 32°F to 104°F (0°C to 40°C) |
| Operating relative humidity | 5% to 95%, noncondensing |
| Nonoperating/Storage temperature | -40°F to 158°F (-40°C to 70°C) |
| Nonoperating/Storage relative humidity | 5% to 95%, noncondensing |
| Altitude | up to 16,404 ft (5 km) |
| Acoustic | No Fan |
| Electrical characteristics | |
| Frequency | 50/60 Hz |
| Voltage | 100 - 240 VAC, rated |
| Maximum power rating | 15 W |
| Notes | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| Safety | IEC 60950-1; EN 60950-1; CSA 22.2 60950-1; UL 60950-1 2nd Edition |
| Emissions | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A |
| Services | Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. |

HPE OfficeConnect 1620 48G Switch (JG914A)

| | |
|-----------------------------------|--|
| I/O ports and slots | 48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |
| Additional ports and slots | 1 RJ-45 console port to access limited CLI port |
| Physical characteristics | |
| Dimensions | 17.32(w) x 9.37(d) x 1.73(h) in (43.99 x 23.8 x 4.39 cm) |
| Weight | 7.28 lb (3.3 kg) |

Technical Specifications

| | | |
|-----------------------------------|--|---|
| Memory and processor | MIPS @ 650 MHz, 32 MB flash, 128 MB SDRAM; packet buffer size: 512 KB 1.5 MB | |
| Mounting and enclosure | Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included) | |
| Performance | 100 Mb Latency | < 7 μ s |
| | 1000 Mb Latency | < 5 μ s |
| | Throughput | up to 71.4 Mpps (64-byte packets) |
| | Switching capacity | 96 Gbps |
| | MAC address table size | 16384 entries |
| Reliability | MTBF (years) | 81.30 |
| Environment | Operating temperature | 32°F to 104°F (0°C to 40°C) |
| | Operating relative humidity | 5% to 95%, noncondensing |
| | Nonoperating/Storage temperature | -40°F to 158°F (-40°C to 70°C) |
| | Nonoperating/Storage relative humidity | 5% to 95%, noncondensing |
| | Altitude | up to 16,404 ft (5 km) |
| | Acoustic | Power: 49.7 dB, Pressure: 49.7 dB; ISO 7779 |
| Electrical characteristics | Frequency | 50/60 Hz |
| | Voltage | 100 - 240 VAC, rated |
| | Maximum power rating | 28.2 W |
| | Notes | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| Safety | IEC 60950-1; EN 60950-1; CSA 22.2 60950-1; UL 60950-1 2nd Edition | |
| Emissions | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A | |
| Services | Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office. | |

Standards and Protocols General protocols

| | |
|-------------------------------------|---|
| (applies to all products in series) | IEEE 802.1D MAC Bridges |
| | IEEE 802.1p Priority |
| | IEEE 802.1Q VLANs |
| | IEEE 802.3 Type 10BASE-T |
| | IEEE 802.3ab 1000BASE-T |
| | IEEE 802.3ad Link Aggregation Control Protocol (LACP) |
| | IEEE 802.3az Energy Efficient Ethernet |
| | IEEE 802.3i 10BASE-T |
| | IEEE 802.3x Flow Control |

| Date | Version History | Action | Description of Change: |
|------|-----------------|--------|------------------------|
|------|-----------------|--------|------------------------|

Summary of Changes

| | | | |
|-------------|---------------------|---------|---|
| 06-May-2016 | From Version 2 to 3 | Changed | Document name changed to HPE OfficeConnect 1620 Switch Series. SKU descriptions, Overview and Technical Specifications updated. |
| 01-Dec-2015 | From Version 1 to 2 | Changed | Overview and Technical Specifications updated |



Sign up for updates

★ Rate this document

© Copyright 2016 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

c04474819 - 15108 - Worldwide - V3 - 06-May-2016

