

Overview

HPE 5500 EI Switch Series

Models

HP 5500-24G EI Switch with 2 Interface Slots	JD377A
HP 5500-48G EI Switch with 2 Interface Slots	JD375A
HP 5500-24G-SFP EI Switch with 2 Interface Slots	JD374A
HP 5500-48G-PoE+ EI Switch with 2 Interface Slots	JG240A
HP 5500-24G-PoE+ EI Switch with 2 Interface Slots	JG241A

Key features

- High expandability for investment protection
- Premium security and integrated management
- Multilayer reliability
- Convergence-ready support
- Outstanding Quality of Service (QoS)

Product overview

These Gigabit Ethernet switches deliver outstanding security, reliability, and multiservice support capabilities for robust switching at the edge or aggregation layer of large enterprise and campus networks, or in the core layer of SMB networks. The HPE 5500 EI Switch Series is comprised of Layer 2/3 Gigabit Ethernet switches that can accommodate the most demanding applications and provide resilient and secure connectivity as well as the latest traffic prioritization technologies to enhance applications on convergent networks. With complete IPv4/IPv6 dual-stack support, the series provides a migration path from IPv4 to IPv6 and has hardware support for IPv6. Designed for increased flexibility, these switches are available with 24 or 48 Gigabit Ethernet ports. Power over Ethernet (PoE) and non-PoE models are available with optional GbE and 10GbE expansion capability. The all-fiber model with dual power supplies is ideal for applications that require the highest availability.

Features and benefits

Software-defined networking

- **OpenFlow**
supports OpenFlow 1.0 and 1.3 specifications to enable SDN by allowing separation of the data (packet forwarding) and control (routing decision) paths

Quality of Service (QoS)

- **Storm restraint:** allows limitation of broadcast, multicast, and unknown unicast traffic rate to cut down on unwanted broadcast traffic on the network
- **Advanced classifier-based QoS:** classifies traffic using multiple match criteria based on Layer 2, 3, and 4 information; applies QoS policies such as setting priority level and rate limit to bi-directional selected traffic on a per-port, per-VLAN, or whole switch basis
- **Powerful QoS feature:** creates traffic classes based on ACLs, IEEE 802.1p precedence, IP, DSCP or ToS precedence; supports filter, redirect, mirror, or remark; supports the following congestion actions: strict priority queuing (SP), weighted round robin (WRR), SP+WRR, weighted fair queuing (WFQ), and weighted random early discard (WRED)

Overview

- **Traffic policing:** supports Committed Access Rate (CAR) and line rate

Management

- **Friendly port names:** allow assignment of descriptive names to ports
- **Remote configuration and management:** is available through a secure Web browser or a CLI
- **Manager and operator privilege levels:** enable read-only (operator) and read-write (manager) access on CLI and Web browser management interfaces
- **Command authorization:** leverages HWTACACS to link a custom list of CLI commands to an individual network administrator's login; also provides an audit trail
- **Secure Web GUI:** provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **Dual flash images:** provide independent primary and secondary operating system files for backup while upgrading
- **Multiple configuration files:** can be stored to the flash image
- **Complete session logging:** provides detailed information for problem identification and resolution
- **SNMPv1, v2c, and v3:** facilitate centralized discovery, monitoring, and secure management of networking devices
- **Remote monitoring (RMON):** uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications
- **sFlow (RFC 3176):** provides scalable ASIC-based wirespeed network monitoring and accounting with no impact on network performance; this allows network operators to gather a variety of sophisticated network statistics and information for capacity planning and real-time network monitoring purposes
- **Management VLAN:** segments traffic to and from management interfaces, including CLI/telnet, a Web browser interface, and SNMP
- **Remote Intelligent Mirroring:** mirrors ingress/egress ACL-selected traffic from a switch port or VLAN to a local or remote switch port anywhere on the network
- **Device Link Detection Protocol (DLDP):** monitors a cable between two switches and shuts down the ports on both ends if the cable is broken, preventing network problems such as loops
- **IPv6 management:** provides future-proof networking because the switch is capable of being managed whether the attached network is running IPv4 or IPv6; supports pingv6, tracertv6, Telnetv6, TFTPv6, DNSv6, syslogv6, FTPv6, SNMPv6, DHCPv6, and RADIUS for IPv6
- **Troubleshooting:** ingress and egress port monitoring enable network problem solving; virtual cable tests provide visibility into cable problems
- **In-Service Software Upgrade (ISSU):** enables operators to perform upgrades in the shortest possible amount of time with minimal risk to network operations or traffic disruptions

Connectivity

- **Auto-MDIX:** automatically adjusts for straight-through or crossover cables on all 10/100/1000 ports
- **Flow control:** provides back pressure using standard IEEE 802.3x, reducing congestion in heavy traffic situations
- **Jumbo packet support:** supports up to 9216-byte frame size to improve the performance of large data transfers
- **Optional 10 GbE ports:** deliver, through the use of optional modules, additional 10GbE connections, which are available for uplinks or high-bandwidth server connections; flexibly support copper, XFP, SFP+, or CX4 local connections
- **High-density port connectivity:** provides up to 48 fixed 10/100/1000BASE-T or 24 SFP 100/1000BASE-X ports in a Layer 2/Layer 3 stackable switch supporting unique IRF stacking
- **IEEE 802.3at Power over Ethernet (PoE+) support:** simplifies deployment and dramatically reduces installation costs by helping to eliminate the time and cost involved in supplying local power at each access point location
- **Ethernet operations, administration and maintenance (OAM):** detects data link layer problems that occurred in the "last mile" using the IEEE 802.3ah OAM standard; monitors the status of the link between two devices

Overview

- **High-bandwidth CX4 and SFP+ local stacking:** provide 10 Gb/s SFP+ or 12 Gb/s CX4 local stacking cables; achieve a resilient stacking configuration

Performance

- **Nonblocking architecture**
up to 192 Gb/s nonblocking switching fabric provides wire-speed switching with up to 143 million pps throughput
- **Hardware-based wirespeed access control lists (ACLs)**
help provide high levels of security and ease of administration without impacting network performance with a feature-rich TCAM-based ACL implementation

Resiliency and high availability

- **Separate data and control paths:** keeps control separated from services and keeps service processing isolated; increases security and performance
- **External redundant power supply:** provides high reliability
- **Smart link:** allows 50 ms failover between links
- **Spanning Tree/MSTP, RSTP:** provides redundant links while preventing network loops
- **Rapid Ring Protection Protocol (RRPP):** connects multiple switches in a high-performance ring using standard Ethernet technology; traffic can be rerouted around the ring in less than 50 ms, reducing the impact on traffic and applications
- **Virtual Router Redundancy Protocol (VRRP):** allows a group of routers to dynamically back each other up to create highly available routed environments
- **Intelligent Resilient Fabric (IRF):** creates virtual resilient switching fabrics, where two or more switches perform as a single L2 switch and L3 router; switches do not have to be co-located and can be part of a disaster recovery system; servers or switches can be attached using standard LACP for automatic load balancing and high availability; can eliminate the need for complex protocols like Spanning Tree Protocol, Equal-Cost Multipath (ECMP), or VRRP, thereby simplifying network operation
- **IP Fast Reroute (FRR):** forms backup paths and allows 50 ms switchover in case of a main path fault

Layer 2 switching

- **32K MAC addresses:** provide access to many Layer 2 devices
- **IEEE 802.1ad QinQ and Selective QinQ:** increase the scalability of an Ethernet network by providing a hierarchical structure; connect multiple LANs on a high-speed campus or metro network
- **GARP VLAN Registration Protocol:** allows automatic learning and dynamic assignment of VLANs
- **IEEE 802.1ad QinQ:** increases the scalability of an Ethernet network by providing a hierarchical structure; connects multiple LANs on a high-speed campus or metro network
- **10 GbE port aggregation:** allows grouping of ports to increase overall data throughput to a remote device
- **Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping:** effectively control and manage the flooding of multicast packets in a Layer 2 network

Layer 3 services

- **Address Resolution Protocol (ARP):** determines the MAC address of another IP host in the same subnet
- **Dynamic Host Configuration Protocol (DHCP):** simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets
- **Loopback interface address:** defines an address in Routing Information Protocol (RIP) and Open Standard Path First (OSPF), improving diagnostic capability
- **User Datagram Protocol (UDP) helper function:** allows UDP broadcasts to be directed across router interfaces to

Overview

specific IP unicast or subnet broadcast addresses and prevents server spoofing for UDP services such as DHCP

- **Route maps:** provide more control during route redistribution; allow filtering and altering of route metrics

Layer 3 routing

- **IPv4 routing protocols:** support static routes, RIP, OSPF, ISIS, and BGP
- **IPv6 routing protocols:** provide routing of IPv6 at wire speed; support static routes, RIPng, OSPFv3, IS-ISv6, and BGP4+ for IPv6
- **Equal-Cost Multipath (ECMP):** enables multiple equal-cost links in a routing environment to increase link redundancy and scale bandwidth
- **Policy-based routing:** makes routing decisions based on policies set by the network administrator
- **IGMPv1, v2, and v3:** allow individual hosts to be registered on a particular VLAN
- **PIM-SSM, PIM-DM, and PIM-SM (for IPv4 and IPv6):** support IP Multicast address management and inhibition of DoS attacks
- **IPv6 tunneling:** allows a smooth transition from IPv4 to IPv6 by encapsulating IPv6 traffic over an existing IPv4 infrastructure
- **Unicast Reverse Path Forwarding (uRPF):** is defined by RFC 3704 and limits erroneous or malicious traffic
- **Bidirectional Forwarding Detection (BFD):** enables link connectivity monitoring and reduces network convergence time for RIP, OSPF, BGP, IS-IS, VRRP, and IRF

Security

- **Access control lists (ACLs):** provide IP Layer 2 to Layer 4 traffic filtering; support global ACL, VLAN ACL, port ACL, and IPv6 ACL. Up to 3072 ingress ACLs and 448 egress ACLs are supported.
- **IEEE 802.1X:** is an industry-standard method of user authentication that uses an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server
- **MAC-based authentication:** authenticates the client with the RADIUS server based on the client's MAC address
- **Identity-driven security and access control:**
 - **Per-user ACLs:** permit or deny user access to specific network resources based on user identity and time of day, allowing multiple types of users on the same network to access specific network services without risking network security or providing unauthorized access to sensitive data
 - **Automatic VLAN assignment:** automatically assigns users to the appropriate VLAN based on their identities
- **Secure management access:** securely encrypts all access methods (CLI, GUI, or MIB) through SSHv2, SSL, and/or SNMPv3
- **Secure FTP:** allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- **Guest VLAN:** provides a browser-based environment to authenticated clients that is similar to IEEE 802.1X
- **Endpoint Admission Defense (EAD):** provides security policies to users accessing a network
- **Port security:** allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **Port isolation:** secures and adds privacy, and prevents malicious attackers from obtaining user information
- **STP BPDU port protection:** blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **STP Root Guard:** protects the root bridge from malicious attack or configuration mistakes
- **DHCP protection:** blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **Dynamic ARP protection:** blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **IP source guard:** helps prevent IP spoofing attacks
- **RADIUS/HWTACACS:** eases switch management security administration by using a password authentication server
- **Multiple Customer Edge (MCE):** facilitates MPLS VPN network integration with up to 64 VPNs support

Overview

- **Unicast Reverse Path Forwarding (URPF):** allows normal packets to be forwarded correctly, whereas the attaching packet will be discarded due to lack of reverse path route or incorrect inbound interface; prevents source spoofing and distributed attacks; supports distributed URPF

Convergence

- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** facilitates easy mapping using network management applications with LLDP automated device discovery protocol
- **LLDP-MED:** is a standard extension that automatically configures network devices, including LLDP-capable IP phones
- **LLDP-CDP compatibility:** receives and recognizes CDP packets from Cisco's IP phones for seamless interoperation
- **IEEE 802.3af Power over Ethernet:** provides up to 15.4 W per port to PoE-powered devices such as IP phones, wireless access points, and video cameras
- **PoE allocations:** supports multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user-specified) to allocate PoE power for more efficient energy savings
- **Voice VLAN:** automatically assigns VLAN and priority for IP phones, simplifying network configuration and maintenance
- **IP multicast snooping (data-driven IGMP):** prevents flooding of IP multicast traffic
- **Internet Group Management Protocol (IGMP):** utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks; supports IGMPv1, v2, and v3
- **Protocol Independent Multicast (PIM):** defines modes of Internet multicasting to allow one-to-many and many-to-many transmission of information; supports PIM Dense Mode (DM), Sparse Mode (SM), and Source-Specific Mode (SSM)
- **Multicast Source Discovery Protocol (MSDP):** allows multiple PIM-SM domains to interoperate; is used for inter-domain multicast applications
- **Multicast Border Gateway Protocol (MBGP):** allows multicast traffic to be forwarded across BGP networks and kept separate from unicast traffic
- **Multicast VLAN:** allows multiple VLANs to receive the same IPv4 or IPv6 multicast traffic, lessening network bandwidth demand by reducing or eliminating multiple streams to each VLAN

Device support

- **Cisco prestandard PoE support:** detects and provides power to Cisco's prestandard PoE devices such as wireless LAN access points and IP phones

Additional information

- **Green IT and power:** use the latest advances in silicon development, shut off unused ports, and use variable-speed fans to improve energy efficiency
- **Green initiative support:** provides support for RoHS and WEEE regulations

Warranty and support

- **Limited Lifetime Warranty**
see <http://www.hpe.com/networking/warrantysummary> for warranty and support information included with your product purchase.
- **Software releases**
to find software for your product, refer to <http://www.hpe.com/networking/support>; for details on the software releases available with your product purchase, refer to <http://www.hpe.com/networking/warrantysummary>

Configuration

Build To Order: BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

Switch Chassis

HP 5500-24G EI Switch	JD377A
<ul style="list-style-type: none"> • 24 RJ-45 autosensing 10/100/1000 ports • 4 dual-personality ports; autosensing 10/100/1000Base-T or SFP • min=0 \ max=4 SFP Transceivers • 2 port expansion module slots • Power Supply included • 1U - Height 	See Configuration NOTE: 1, 3
PDU CABLE NA/MEX/TW/JP	JD377A#B2B
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU CABLE ROW	JD377A#B2C
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	
High Volt Switch to Wall Power Cord	JD377A#B2E
<ul style="list-style-type: none"> • NEMA L6-20P Cord (NA/MEX/JP/TW) 	
HP 5500-24G-SFP EI Switch	JD374A
<ul style="list-style-type: none"> • 24 fixed Gigabit Ethernet SFP ports • (Of the 24, 8 are dual-personality ports; autosensing 10/100/1000Base-T or SFP) • min=0 \ max=2432 SFP Transceivers • 2 - port expansion module slots • 1 - JD362A - HP 5500 150WAC Power Supply Included • 1U - Height 	See Configuration NOTE: 1, 3
PDU CABLE NA/MEX/TW/JP	JD374A#B2B
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU CABLE ROW	JD374A#B2C
<ul style="list-style-type: none"> • C15 PDU Jumper Cord (ROW) 	
High Volt Switch to Wall Power Cord	JD374A#B2E

Configuration

- NEMA L6-20P Cord (NA/MEX/JP/TW)

HP 5500-24G-PoE+ EI Switch w/2 Intf Slts

- 24 RJ-45 autosensing 10/100/1000 PoE+ports
- 4 dual-personality ports; autosensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- Power Supply included
- 1U - Height

JG241A
See
Configuration
NOTE:1, 3

PDU CABLE NA/MEX/TW/JP

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

JG241A#B2B

PDU CABLE ROW

- C15 PDU Jumper Cord (ROW)

JG241A#B2C

High Volt Switch to Wall Power Cord

- NEMA L6-20P Cord (NA/MEX/JP/TW)

JG241A#B2E

HP 5500-48G EI Switch

- 48 RJ-45 autosensing 10/100/1000 ports
- 4 dual-personality ports; autosensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- Power Supply included
- 1U - Height

JD375A
See
Configuration
NOTE:1, 3

PDU CABLE NA/MEX/TW/JP

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

JD375A#B2B

PDU CABLE ROW

- C15 PDU Jumper Cord (ROW)

JD375A#B2C

High Volt Switch to Wall Power Cord

- NEMA L6-20P Cord (NA/MEX/JP/TW)

JD375A#B2E

HP 5500-48G-PoE+ EI Switch w/2 Intf Slts

- 48 RJ-45 autosensing 10/100/1000 PoE+ ports

JG240A
See

Configuration

- 4 dual-personality ports; autosensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- Power Supply included
- 1U - Height

Configuration
NOTE:1, 3

PDU CABLE NA/MEX/TW/JP

JG240A#B2B

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

PDU CABLE ROW

JG240A#B2C

- C15 PDU Jumper Cord (ROW)

High Volt Switch to Wall Power Cord

JG240A#B2E

- NEMA L6-20P Cord (NA/MEX/JP/TW)

Configuration Rules:

Note 1	The following Transceivers install into this Switch	
	HP X120 1G SFP LC SX Transceiver	JD118B
	HP X120 1G SFP LC LX Transceiver	JD119B
	HP X120 1G SFP LC BX 10-U Transceiver	JD098B
	HP X120 1G SFP LC BX 10-D Transceiver	JD099B
	HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
	HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
	HP X125 1G SFP LC LH70 Transceiver	JD063B
	HP X115 100M SFP LC FX Transceiver	JD102B
	HP X110 100M SFP LC LX Transceiver	JD120B
	HP X110 100M SFP LC LH40 Transceiver	JD090A
	HP X110 100M SFP LC LH80 Transceiver	JD091A
	HP X120 1G SFP RJ45 T Transceiver	JD089B

Note 3 Localization (Wall Power Cord) required on orders without #B2B, #B2C (PDU Power Cord) or #B2E. (See Localization Menu)

Remarks Drop down under power supply should offer the following options and results:
Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)
Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)
High Volt Switch/Router/Power Supply to Wall Power Cord - #B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)

Configuration

Box Level Integration CTO Models

CTO Solution Sku

HP 55xx CTO Switch Solution

JG506A

- SSP trigger sku

CTO Base Sku

HP 5500-24G EI Switch - CTO

JD377A

- 24 RJ-45 autosensing 10/100/1000 ports
- 4 dual-personality ports; autosensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 - port expansion module slots
- Power Supply Included
- 1U - Height

See Configuration

NOTE:1, 3, 6,7

PDU Cable NA/MEX/TW/JP

JD377A#B2B

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

PDU Cable ROW

JD377A#B2C

- C15 PDU Jumper Cord (ROW)

High Volt Switch to Wall Power Cord

JD377A#B2E

- NEMA L6-20P Cord (NA/MEX/JP/TW)

HP 5500-24G-SFP EI Switch - CTO

JD374A

- 24 fixed Gigabit Ethernet SFP ports
- 8 dual-personality ports; autosensing 10/100/1000Base-T or SFP
- min=0 \ max=32 SFP Transceivers
- 2 - port expansion module slots
- 1 - JD362A - HP 5500 150WAC Power Supply Included
- 1U - Height

See Configuration

NOTE:1, 3, 6,7

PDU Cable NA/MEX/TW/JP

JD374A#B2B

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

PDU Cable ROW

JD374A#B2C

- C15 PDU Jumper Cord (ROW)

Configuration

High Volt Switch to Wall Power Cord	JD374A#B2E
<ul style="list-style-type: none">NEMA L6-20P Cord (NA/MEX/JP/TW)	
HP 5500-24G-PoE+ EI Switch w/2 Intf Slts - CTO	JG241A
<ul style="list-style-type: none">24 RJ-45 autosensing 10/100/1000 PoE+ ports4 dual-personality ports; autosensing10/100/1000Base-T or SFPmin=0 \ max=4 SFP Transceivers2 - port expansion module slotsPower Supply included1U - Height	See Configuration NOTE: 1, 3, 6,7
PDU Cable NA/MEX/TW/JP	JG241A#B2B
<ul style="list-style-type: none">C15 PDU Jumper Cord (NA/MEX/TW/JP)	
PDU Cable ROW	JG241A#B2C
<ul style="list-style-type: none">C15 PDU Jumper Cord (ROW)	
High Volt Switch to Wall Power Cord	JG241A#B2E
<ul style="list-style-type: none">NEMA L6-20P Cord (NA/MEX/JP/TW)	
HP 5500-48G EI Switch - CTO	JD375A
<ul style="list-style-type: none">48 RJ-45 autosensing 10/100/1000 ports4 dual-personality ports; autosensing10/100/1000Base-T or SFPmin=0 \ max=4 SFP Transceivers2 - port expansion module slotsPower Supply included1U - Height	See Configuration NOTE: 1, 3, 6,7
PDU Cable NA/MEX/TW/JP	JD375A#B2B
<ul style="list-style-type: none">C15 PDU Jumper Cord (NA/MEX/TW/JP)	
PDU Cable ROW	JD375A#B2C
<ul style="list-style-type: none">C15 PDU Jumper Cord (ROW)	
High Volt Switch to Wall Power Cord	JD375A#B2E
<ul style="list-style-type: none">NEMA L6-20P Cord (NA/MEX/JP/TW)	

Configuration

HP 5500-48G-PoE+ EI Switch w/2 Intf Slts - CTO	JG240A
<ul style="list-style-type: none"> 48 RJ-45 autosensing 10/100/1000 PoE+ ports 4 dual-personality ports; autosensing 10/100/1000Base-T or SFP min=0 \ max=4 SFP Transceivers 2 - port expansion module slots Power Supply included 1U - Height 	See Configuration NOTE: 1, 3, 6,7
PDU Cable NA/MEX/TW/JP	JG240A#B2B
<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU Cable ROW	JG240A#B2C
<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
High Volt Switch to Wall Power Cord	JG240A#B2E
<ul style="list-style-type: none"> NEMA L6-20P Cord (NA/MEX/JP/TW) 	

Configuration Rules:

Note 1	The following Transceivers install into this Switch : (Use #OD1 if switch is CTO)	
	HP X120 1G SFP LC SX Transceiver	JD118B
	HP X120 1G SFP LC LX Transceiver	JD119B
	HP X120 1G SFP LC BX 10-U Transceiver	JD098B
	HP X120 1G SFP LC BX 10-D Transceiver	JD099B
	HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
	HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
	HP X125 1G SFP LC LH70 Transceiver	JD063B
	HP X115 100M SFP LC FX Transceiver	JD102B
	HP X110 100M SFP LC LX Transceiver	JD120B
	HP X110 100M SFP LC LH40 Transceiver	JD090A
	HP X110 100M SFP LC LH80 Transceiver	JD091A
	HP X120 1G SFP RJ45 T Transceiver	JD089B
Note 3	Localization (Wall Power Cord) required on orders without #B2B, #B2C (PDU Power Cord) or #B2E. (See Localization Menu)	
Note 6	If this Switch is selected, Then a Minimum of 1 factory integrated accessory must be ordered and integrated to CTO chassis. See Menu below, option must have a #OD1 to be integrated to the CTO Chassis.	
Note 7	If the Switch Chassis is to be Box Level Factory Integrated (CTO), Then the #OD1 is required on the Switch Chassis and integrated to the JG506A - HP 55xx CTO Enablement. (Min 1/Max 1 Switch per SSP)	

Configuration

Remark:

Drop down under power supply should offer the following options and results:

Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)

Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)

High Volt Switch/Router/Power Supply to Wall Power Cord - #B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)

Rack Level Integration CTO Models

Switch Chassis

HP 5500-24G EI Switch

- 24 RJ-45 autosensing 10/100/1000 ports
- 4 dual-personality ports; autosensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- Power Supply included
- 1U - Height

JD377A

See Configuration

NOTE:1, 3, 10

PDU CABLE NA/MEX/TW/JP

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

JD377A#B2B

PDU CABLE ROW

- C15 PDU Jumper Cord (ROW)

JD377A#B2C

HP 5500-24G-SFP EI Switch

- 24 fixed Gigabit Ethernet SFP ports
- (Of the 24, 8 are dual-personality ports; autosensing 10/100/1000Base-T or SFP)
- min=0 \ max=2432 SFP Transceivers
- 2 port expansion module slots
- 1 - JD362A - HP 5500 150WAC Power Supply Included
- 1U - Height

JD374A

See Configuration

NOTE:1, 3, 10

PDU CABLE NA/MEX/TW/JP

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

JD374A#B2B

PDU CABLE ROW

JD374A#B2C

Configuration

- C15 PDU Jumper Cord (ROW)

HP 5500-24G-PoE+ EI Switch w/2 Intf Slts

- 24 RJ-45 autosensing 10/100/1000 PoE+ports
- 4 dual-personality ports; autosensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- Power Supply included
- 1U - Height

JG241A

See Configuration

NOTE:1, 3, 10

PDU CABLE NA/MEX/TW/JP

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

JG241A#B2B

PDU CABLE ROW

- C15 PDU Jumper Cord (ROW)

JG241A#B2C

HP 5500-48G EI Switch

- 48 RJ-45 autosensing 10/100/1000 ports
- 4 dual-personality ports; autosensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- Power Supply included
- 1U - Height

JD375A

See Configuration

NOTE:1, 3, 10

PDU CABLE NA/MEX/TW/JPC

- 15 to C14 Jumper Cord (NA)

JD375A#B2B

PDU CABLE ROW

- C15 PDU Jumper Cord (ROW)

JD375A#B2C

HP 5500-48G-PoE+ EI Switch w/2 Intf Slts

- 48 RJ-45 autosensing 10/100/1000 PoE+ports
- 4 dual-personality ports; autosensing 10/100/1000Base-T or SFP
- min=0 \ max=4 SFP Transceivers
- 2 port expansion module slots
- Power Supply included
- 1U - Height

JG240A

See Configuration

NOTE:1, 3, 10

Configuration

PDU CABLE NA/MEX/TW/JP JG240A#B2B

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

PDU CABLE ROW JG240A#B2C

- C15 PDU Jumper Cord (ROW)

Configuration Rules:

Note 1 The following Transceivers install into this Switch: (Use #0D1 if switch is CTO)

HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X120 1G SFP LC BX 10-U Transceiver	JD098B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B
HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X115 100M SFP LC FX Transceiver	JD102B
HP X110 100M SFP LC LX Transceiver	JD120B
HP X110 100M SFP LC LH40 Transceiver	JD090A
HP X110 100M SFP LC LH80 Transceiver	JD091A
HP X120 1G SFP RJ45 T Transceiver	JD089B

Note 3 Localization (Wall Power Cord) required on orders without #B2B, #B2C (PDU Power Cord) . (See Localization Menu)

REMARK: When Switches/Routers are Factory Racked, Then #B2B, or #B2C should be the Defaulted Power Cable option on the Switches/Routers.

Note 10 If HP CTO Switch Chassis is selected for Rack Level Integration, Then the Switch needs to integrate (with #0D1) to the Rack.

Remarks:

Drop down under power supply should offer the following options and results:

Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)

Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)"

Enter the following menu selections as integrated to the CTO Model X above if order is factory built.

Configuration

Internal Power Supplies

(JD374A and JG249A Switches Only) (std 1 // max 2) User Selection (min 0 // max 1) per switch enclosure

HP 5500 150WDC Power Supply

JD366A

See Configuration

NOTE: 4

HP 5500 150WAC Power Supply

JD362A

See Configuration

- includes 1 x c13, 910w

NOTE:1, 2,3,4

PDU CABLE NA/MEX/TW/JP

JD362A#B2B

- C15 PDU Jumper Cord (NA/MEX/TW/JP)

PDU CABLE ROW

JD362A#B2C

- C15 PDU Jumper Cord (ROW)

High Volt Switch to Wall Power Cord

JD362A#B2E

- NEMA L6-20P Cord (NA/MEX/JP/TW)

Configuration Rules:

Note 2 If #B2E is selected Then replace Localized option with #B2E for power supply and with #B2E for switch . (Offered only in AMS, Taiwan, and Japan)

Note 3 Localization (Wall Power Cord) required on orders without #B2B, #B2C (PDU Power Cord) . (See Localization Menu)

REMARK: When Switches/Routers are Factory Racked, Then #B2B, or #B2C should be the Defaulted Power Cable option on the Switches/Routers.

Note 4 Not supported on JD377A, JG241A, JD375A, JG240A, JG251A, JG250A, JG252A, JG253A

Remarks: If Power Supply is added to switch with power supply, then Switch and Power Supply localization must match.

Drop down under power supply should offer the following options and results:

Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)

Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)

High Volt Switch/Router/Power Supply to Wall Power Cord - #B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)

Configuration

Switch Enclosure Options

External Redundant Power Supplies

HP RPS 800 Redundant Power Supply

- Height = 1U
- includes 1 x c13

JD183A

See Configuration

NOTE:2,4,6

HP RPS1600 Redundant Power System

- Height = 1U
includes 1 x c13, 1600w and Power Supply port

JG136A

See Configuration

NOTE:2, 3,5

HP RPS1600 1600W AC Power Supply

- Installs into JG136A only

JG137A

See Configuration

NOTE:1, 3

Configuration Rules:

- Note 1 If this power supply is selected, The JG136A - HP A-RPS1600 Redundant Power System must be on order or onsite.
- Note 2 Localization required.
- Note 3 Each switch will only support 1 JG136A and 1 JG137A Power supply systems.
- Note 4 Supported only on the JD377A, JG250A, JD375A and JG251A Switches
- Note 5 Supported only on the JG241A, JG252A, JG240A and JG253A Switches
- Note 6 Each switch will only support 1 JD183A Power supply.

Options for the HPN 5500 Power Supplies

HP X290 1000 A JD5 2m RPS Cable

JD187A

HP X290 1000 A JD5 Non-PoE 2m RPS Cable

JD188A

HP X290 1000 B JD5 2m RPS Cable

JD189A

HP X290 500/800 1m RPS Cable

JD190A

HP X290 500 U 1m RPS Cable

JD185A

Remarks: These cables are used to connect the External Power System to Switch.

Modules

Configuration

(std 0 // max 2) User Selection (min 0 // max 2) per switch enclosure

HP 5500 2-port 10GbE XFP Module	JD359B
<ul style="list-style-type: none"> min=0 \ max=2 XFP Transceivers 	See Configuration NOTE: 2, 5, 6
HP 5500 2-port 10GbE Local Connect Mod	JD360B
<ul style="list-style-type: none"> min=0 \ max=2 CX4 Cables 	See Configuration NOTE: 4, 5, 6
HP 5500 1-port 10GbE XFP Module	JD361B
<ul style="list-style-type: none"> min=0 \ max=1 XFP Transceivers 	See Configuration NOTE: 2, 5, 6
HP 5500/5120 2-port 10GbE SFP+ Module	JD368B
<ul style="list-style-type: none"> min=0 \ max=2 SFP+ Transceivers 	See Configuration NOTE: 1, 5, 6
HP 5500/4800 2-port GbE SFP Module	JD367A
<ul style="list-style-type: none"> min=0 \ max=2 SFP Transceivers 	See Configuration NOTE: 3, 5, 6
HP 5500/5120 2p 10GBASE-T Module	JG535A
<ul style="list-style-type: none"> No Transceivers 	See Configuration NOTE: 5, 6

Configuration Rules:

Note 1	The following Transceivers install into this Module: (Use #OD1 or #B01 if switch is CTO)	
	HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
	HP X130 10G SFP+ LC SR Transceiver	JD092B
	HP X130 10G SFP+ LC LRM Transceiver	JD093B
	HP X130 10G SFP+ LC LR Transceiver	JD094B
	HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095C
	HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096C
	HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097C
	HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable	JG081C
	HP X240 10G SFP+ SFP+ 7m Direct Attach Copper Cable	JC784C
Note 2	The following Transceivers install into this Module: (Use #OD1 if switch is CTO)	
	HP X135 10G XFP LC ER Transceiver	JD121A
	HP X130 10G XFP LC LR Single Mode 10km 1310nm Transceiver	JD108B
	HP X130 10G XFP LC SR Transceiver	JD117B
Note 3	The following Transceivers install into this Module: (Use #OD1 if switch is CTO)	

Configuration

HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X120 1G SFP LC BX 10-U Transceiver	JD098B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B
HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X115 100M SFP LC FX Transceiver	JD102B
HP X110 100M SFP LC LX Transceiver	JD120B
HP X110 100M SFP LC LH40 Transceiver	JD090A
HP X110 100M SFP LC LH80 Transceiver	JD091A
HP X120 1G SFP RJ45 T Transceiver	JD089B

Note 4 The following Cables install into this Module: (Use #B01 if switch is CTO)

HP X230 Local Connect 50cm CX4 Cable	JD363B
HP X230 Local Connect 100cm CX4 Cable	JD364B
HP X230 CX4 to CX4 3m Cable	JD365A

NOTE: Two JD365A - HP X230 CX4 to CX4 3m Cable should be added by default if Module is selected.

Note 5 If factory intergrated into the switch, This Module must be ordered as #OD1 when the switch is not Factory Racked.

Note 6 If factory intergrated into the switch, This Module must be ordered as #B01 when the switch is Factory Racked (Rack Level Integration CTO).

Transceivers

SFP Transceivers

HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X120 1G SFP LC BX 10-U Transceiver	JD098B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B
HP X115 100M SFP LC FX Transceiver	JD102B
HP X110 100M SFP LC LX Transceiver	JD120B
HP X110 100M SFP LC LH40 Transceiver	JD090A
HP X110 100M SFP LC LH80 Transceiver	JD091A
HP X120 1G SFP RJ45 T Transceiver	JD089B

SFP+ Transceivers

Configuration

HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
HP X130 10G SFP+ LC SR Transceiver	JD092B
HP X130 10G SFP+ LC LRM Transceiver	JD093B
HP X130 10G SFP+ LC LR Transceiver	JD094B
HP X240 10G SFP+ SFP+ 0.65m DAC Cable	JD095C#B01
HP X240 10G SFP+ SFP+ 1.2m DAC Cable	JD096C#B01
HP X240 10G SFP+ SFP+ 3m DAC Cable	JD097C#B01
HP X240 10G SFP+ SFP+ 5m DAC Cable	JG081C #B01
HP X240 10G SFP+ 7m DAC Cable	JC784C #B01

XFP Transceivers

HP X130 10G XFP LC LR Single Mode 10km 1310nm Transceiver	JD108B
HP X130 10G XFP LC SR Transceiver	JD117B
HP X135 10G XFP LC ER Transceiver	JD121A

Cables

Local Connect Cables

HP X230 Local Connect 50cm CX4 Cable	JD363B#B01
HP X230 Local Connect 100cm CX4 Cable	JD364B#B01
HP X230 CX4 to CX4 3m Cable	JD365A#B01

Multi-Mode Cables

HP LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
HP LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
HP LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable	AJ835A
HP LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
HP LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
HP LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
HP LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A

Opacity Shield Kit

System (std 0 // max 1) User Selection (min 0 // max 1)

Configuration

HP 5500/5120 Gig-T EI Opcty Shld Kit

- Supported on JG250A, JG251A

JG557A

See Configuration

NOTE:1

HP 5500/5120 Gig-T PoE EI Opcty Shld Kit

- Supported on JG252A, JG253A

JG559A

See Configuration

NOTE:1

HP 5500-24G-SFP EI Opcty Shld Kit

- Supported on JG249A

JG558A

See Configuration

NOTE:1

Configuration Rules:

Note 1 If selected with a CTO Switch Solution, Quantity 1 of JG585A#B01 must also be ordered.

Tamper Evidence Labels

System (std 0 // max 1) User Selection (min 0 // max 1)

HP 12mm x 60mm Tmpr-Evidence (30) Lbl

- Supported on JG557A, JG559A or JG558A

JG585A

See Configuration

NOTE:1

Configuration Rules:

Note 1 If selected with a CTO Switch Solution, Quantity 1 of JG557A#B01, JG558A#B01 or JG559A#B01 must also be ordered.

Remarks: Each JG557A, JG559A or JG558A would use 1 of JG585A.

Technical Specifications

HP 5500-24G EI Switch with 2 Interface Slots (JD377A)

Ports	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP 2 port expansion module slots 1 RJ-45 serial console port Supports a maximum of 24 autosensing 10/100/1000 ports										
Physical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Dimensions</td> <td>17.32(w) x 11.81(d) x 1.72(h) in (44 x 30 x 4.36 cm) (1U height)</td> </tr> <tr> <td style="vertical-align: top;">Weight</td> <td>8.82 lb (4 kg)</td> </tr> </table>	Dimensions	17.32(w) x 11.81(d) x 1.72(h) in (44 x 30 x 4.36 cm) (1U height)	Weight	8.82 lb (4 kg)						
Dimensions	17.32(w) x 11.81(d) x 1.72(h) in (44 x 30 x 4.36 cm) (1U height)										
Weight	8.82 lb (4 kg)										
Memory and processor	256 MB SDRAM, 32 MB flash; packet buffer size: 2 MB										
Mounting	Mounts in an EIA standard 19-in. telco rack or equipment cabinet (hardware included)										
Performance	<table border="0"> <tr> <td style="vertical-align: top;">1000 Mb Latency</td> <td>< 3.2 μs</td> </tr> <tr> <td style="vertical-align: top;">10 Gbps Latency</td> <td>< 2.6 μs</td> </tr> <tr> <td style="vertical-align: top;">Throughput</td> <td>107.2 million pps</td> </tr> <tr> <td style="vertical-align: top;">Routing/Switching capacity</td> <td>144 Gb/s</td> </tr> <tr> <td style="vertical-align: top;">Routing table size</td> <td>12000 entries (IPv4)</td> </tr> </table>	1000 Mb Latency	< 3.2 μ s	10 Gbps Latency	< 2.6 μ s	Throughput	107.2 million pps	Routing/Switching capacity	144 Gb/s	Routing table size	12000 entries (IPv4)
1000 Mb Latency	< 3.2 μ s										
10 Gbps Latency	< 2.6 μ s										
Throughput	107.2 million pps										
Routing/Switching capacity	144 Gb/s										
Routing table size	12000 entries (IPv4)										
Environment	<table border="0"> <tr> <td style="vertical-align: top;">Operating temperature</td> <td>32°F to 113°F (0°C to 45°C)</td> </tr> <tr> <td style="vertical-align: top;">Operating relative humidity</td> <td>10% to 90%, noncondensing</td> </tr> <tr> <td style="vertical-align: top;">Nonoperating/Storage temperature</td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td style="vertical-align: top;">Nonoperating/Storage relative humidity</td> <td>5% to 95%, noncondensing</td> </tr> <tr> <td style="vertical-align: top;">Acoustic</td> <td>Low-speed fan: 42.6 dB, High-speed fan: 49.7 dB; ISO 7779</td> </tr> </table>	Operating temperature	32°F to 113°F (0°C to 45°C)	Operating relative humidity	10% to 90%, noncondensing	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	Nonoperating/Storage relative humidity	5% to 95%, noncondensing	Acoustic	Low-speed fan: 42.6 dB, High-speed fan: 49.7 dB; ISO 7779
Operating temperature	32°F to 113°F (0°C to 45°C)										
Operating relative humidity	10% to 90%, noncondensing										
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)										
Nonoperating/Storage relative humidity	5% to 95%, noncondensing										
Acoustic	Low-speed fan: 42.6 dB, High-speed fan: 49.7 dB; ISO 7779										
Electrical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Frequency</td> <td>50/60 Hz</td> </tr> <tr> <td style="vertical-align: top;">Maximum heat dissipation</td> <td>375 BTU/hr (395.63 kJ/hr)</td> </tr> <tr> <td style="vertical-align: top;">Voltage</td> <td>100-240 VAC</td> </tr> <tr> <td style="vertical-align: top;">Maximum power rating</td> <td>110 W</td> </tr> <tr> <td style="vertical-align: top;">Notes</td> <td>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</td> </tr> </table>	Frequency	50/60 Hz	Maximum heat dissipation	375 BTU/hr (395.63 kJ/hr)	Voltage	100-240 VAC	Maximum power rating	110 W	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Frequency	50/60 Hz										
Maximum heat dissipation	375 BTU/hr (395.63 kJ/hr)										
Voltage	100-240 VAC										
Maximum power rating	110 W										
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.										
Safety	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11; FDA 21 CFR Subchapter J; ROHS Compliance										
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN										

Technical Specifications

61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A

Management

IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP 5500-48G EI Switch with 2 Interface Slots (JD375A)

Ports

48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only

4 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP

2 port expansion module slots

1 RJ-45 serial console port

Supports a maximum of 48 autosensing 10/100/1000 ports

Physical characteristics

Dimensions 17.32(w) x 11.81(d) x 1.72(h) in (44 x 30 x 4.36 cm) (1U height)

Weight 9.92 lb (4.5 kg)

Memory and processor

256 MB SDRAM, 32 MB flash; packet buffer size: 4 MB

Mounting

Mounts in an EIA standard 19-in. telco rack or equipment cabinet (hardware included)

Performance

1000 Mb Latency < 3.2 μ s

10 Gbps Latency < 2.6 μ s

Throughput 142.9 million pps

Routing/Switching capacity 192 Gb/s

Routing table size 12000 entries (IPv4)

Environment

Operating temperature 32°F to 113°F (0°C to 45°C)

Operating relative humidity 10% to 90%, noncondensing

Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)

Nonoperating/Storage relative humidity 5% to 95%, noncondensing

Acoustic Low-speed fan: 41.3 dB, High-speed fan: 50.1 dB; ISO 7779

Electrical characteristics

Frequency 50/60 Hz

Maximum heat dissipation 528 BTU/hr (557.04 kJ/hr)

Voltage 100-240 VAC

Maximum power rating 155 W

Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Safety

UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2;

Technical Specifications

	IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11; FDA 21 CFR Subchapter J; ROHS Compliance
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4-2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP 5500-24G-SFP EI Switch with 2 Interface Slots (JD374A)

Ports	24 fixed Gigabit Ethernet SFP ports 8 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP 2 port expansion module slots 1 RJ-45 serial console port
Physical characteristics	Dimensions 17.32(w) x 14.17(d) x 1.72(h) in (44 x 36 x 4.36 cm) (1U height) Weight 13.89 lb (6.3 kg)
Memory and processor	256 MB SDRAM, 32 MB flash; packet buffer size: 2 MB
Mounting	Mounts in an EIA standard 19-in. telco rack or equipment cabinet (hardware included)
Performance	1000 Mb Latency < 3.2 μ s 10 Gbps Latency < 2.6 μ s Throughput 107.2 million pps Routing/Switching capacity 144 Gb/s Routing table size 12000 entries (IPv4)
Environment	Operating temperature 32°F to 113°F (0°C to 45°C) Operating relative humidity 10% to 90%, noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 5% to 95%, noncondensing Acoustic Low-speed fan: 45.3 dB, High-speed fan: 50.4 dB; ISO 7779
Electrical characteristics	Frequency 50/60 Hz Maximum heat dissipation 392 BTU/hr (413.56 kJ/hr) Voltage 100-240 VAC Maximum power rating 115 W Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Technical Specifications

Safety	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11; FDA 21 CFR Subchapter J; ROHS Compliance
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
Notes	1 power supply included
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP 5500-48G-PoE+ EI Switch with 2 Interface Slots (JG240A)

Ports	48 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP 2 port expansion module slots 1 RJ-45 serial console port Supports a maximum of 48 autosensing 10/100/1000 ports										
Physical characteristics	<table> <tr> <td>Dimensions</td> <td>17.32(w) x 16.54(d) x 1.72(h) in (43.99 x 42.01 x 4.37 cm) (1U height)</td> </tr> <tr> <td>Weight</td> <td>14.33 lb. (6.5 kg)</td> </tr> </table>	Dimensions	17.32(w) x 16.54(d) x 1.72(h) in (43.99 x 42.01 x 4.37 cm) (1U height)	Weight	14.33 lb. (6.5 kg)						
Dimensions	17.32(w) x 16.54(d) x 1.72(h) in (43.99 x 42.01 x 4.37 cm) (1U height)										
Weight	14.33 lb. (6.5 kg)										
Memory and processor	256 MB SDRAM, 32 MB flash; packet buffer size: 4 MB										
Mounting	Mounts in an EIA standard 19-in. telco rack or equipment cabinet (hardware included)										
Performance	<table> <tr> <td>1000 Mb Latency</td> <td>< 3.2 μs</td> </tr> <tr> <td>10 Gbps Latency</td> <td>< 2.6 μs</td> </tr> <tr> <td>Throughput</td> <td>142.9 million pps</td> </tr> <tr> <td>Routing/Switching capacity</td> <td>192 Gb/s</td> </tr> <tr> <td>Routing table size</td> <td>12000 entries (IPv4)</td> </tr> </table>	1000 Mb Latency	< 3.2 μ s	10 Gbps Latency	< 2.6 μ s	Throughput	142.9 million pps	Routing/Switching capacity	192 Gb/s	Routing table size	12000 entries (IPv4)
1000 Mb Latency	< 3.2 μ s										
10 Gbps Latency	< 2.6 μ s										
Throughput	142.9 million pps										
Routing/Switching capacity	192 Gb/s										
Routing table size	12000 entries (IPv4)										
Environment	<table> <tr> <td>Operating temperature</td> <td>32°F to 113°F (0°C to 45°C)</td> </tr> <tr> <td>Operating relative humidity</td> <td>10% to 90%, noncondensing</td> </tr> <tr> <td>Nonoperating/Storage temperature</td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td>Nonoperating/Storage relative humidity</td> <td>5% to 95%, noncondensing</td> </tr> <tr> <td>Acoustic</td> <td>Low-speed fan: 49.5 dB, High-speed fan: 54.1 dB; ISO 7779</td> </tr> </table>	Operating temperature	32°F to 113°F (0°C to 45°C)	Operating relative humidity	10% to 90%, noncondensing	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	Nonoperating/Storage relative humidity	5% to 95%, noncondensing	Acoustic	Low-speed fan: 49.5 dB, High-speed fan: 54.1 dB; ISO 7779
Operating temperature	32°F to 113°F (0°C to 45°C)										
Operating relative humidity	10% to 90%, noncondensing										
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)										
Nonoperating/Storage relative humidity	5% to 95%, noncondensing										
Acoustic	Low-speed fan: 49.5 dB, High-speed fan: 54.1 dB; ISO 7779										
Electrical characteristics	<table> <tr> <td>Frequency</td> <td>50/60 Hz</td> </tr> <tr> <td>Maximum heat dissipation</td> <td>2255 BTU/hr (2379.02 kJ/hr). Max heat dissipation for AC is 2255 BTU/hr and 3173 BTU/hr for DC.</td> </tr> <tr> <td>Voltage</td> <td>100-240 VAC</td> </tr> </table>	Frequency	50/60 Hz	Maximum heat dissipation	2255 BTU/hr (2379.02 kJ/hr). Max heat dissipation for AC is 2255 BTU/hr and 3173 BTU/hr for DC.	Voltage	100-240 VAC				
Frequency	50/60 Hz										
Maximum heat dissipation	2255 BTU/hr (2379.02 kJ/hr). Max heat dissipation for AC is 2255 BTU/hr and 3173 BTU/hr for DC.										
Voltage	100-240 VAC										

Technical Specifications

DC voltage	-52 to -55 VDC
Maximum power rating	661 W
PoE power	740 W
Notes	<p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> <p>PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS).</p> <p>With AC input, the maximum power consumption is 661 W; PoE is 370 W.</p> <p>With DC input, the maximum power consumption is 930 W; PoE is 740 W.</p>

Safety	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11; FDA 21 CFR Subchapter J; ROHS Compliance
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP 5500-24G-PoE+ EI Switch with 2 Interface Slots (JG241A)

Ports	<p>24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>4 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP</p> <p>2 port expansion module slots</p> <p>1 RJ-45 serial console port</p> <p>Supports a maximum of 24 autosensing 10/100/1000 ports</p>
Physical characteristics	<p>Dimensions 17.32(w) x 16.54(d) x 1.69(h) in (43.99 x 42.01 x 4.29 cm) (1U height)</p> <p>Weight 13.23 lb (6 kg)</p>
Memory and processor	256 MB SDRAM, 32 MB flash; packet buffer size: 2 MB
Mounting	Mounts in an EIA standard 19-in. telco rack or equipment cabinet (hardware included)
Performance	<p>1000 Mb Latency < 3.2 μs</p> <p>10 Gbps Latency < 2.6 μs</p> <p>Throughput 107.2 million pps</p> <p>Routing/Switching capacity 144 Gb/s</p> <p>Routing table size 12000 entries (IPv4)</p>
Environment	<p>Operating temperature 32°F to 113°F (0°C to 45°C)</p> <p>Operating relative 10% to 90%, noncondensing</p>

Technical Specifications

	humidity	
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
	Acoustic	Low-speed fan: 48.1 dB, High-speed fan: 51.1 dB; ISO 7779
Electrical characteristics	Frequency	50/60 Hz
	Maximum heat dissipation	2016 BTU/hr (2126.88 kJ/hr). Max heat dissipation for AC is 2016 BTU/hr and 1678 BTU/hr for DC.
	Voltage	100-240 VAC
	DC Voltage	52 to -55 VDC
	Maximum power rating	591 W
	PoE power	370 W
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS). With AC input, the maximum power consumption is 591 W; PoE is 370 W. With DC input, the maximum power consumption is 492 W; PoE is 370 W.
Safety		UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11; FDA 21 CFR Subchapter J; ROHS Compliance
Emissions		FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4-2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A
Management		IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
Services		Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office
Standards and protocols	BGP	RFC 2464 Transmission of IPv6 over Ethernet Networks
(applies to all products in series)	RFC 1657 Definitions of Managed Objects for BGPv4	RFC 2475 IPv6 DiffServ Architecture
	RFC 1771 BGPv4	RFC 2710 Multicast Listener Discovery (MLD) for IPv6
	RFC 2858 BGP-4 Multi-Protocol Extensions	RFC 2740 OSPFv3 for IPv6
	Device management	RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
	RFC 1157 SNMPv1/v2c	RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only)
	RFC 1256 ICMP Router Discovery Protocol (IRDP)	RFC 2925 Remote Operations MIB (Ping only)
	RFC 1305 NTPv3	RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
	RFC 1901 (Community based SNMPv2)	
	RFC 2452 MIB for TCP6	
	RFC 2454 MIB for UDP6	
	RFC 2573 (SNMPv3 Applications)	

Technical Specifications

RFC 2576 (Coexistence between SNMP V1, V2, V3)
 RFC 2819 RMON
 RFC 3410 (Management Framework)
 RFC 3416 (SNMP Protocol Operations v2)
 RFC 3417 (SNMP Transport Mappings)
 HTML and telnet management
 Multiple Configuration Files
 SNMP v3 and RMON RFC support
 SSHv1/SSHv2 Secure Shell

General protocols

IEEE 802.1ad Q-in-Q
 IEEE 802.1D MAC Bridges
 IEEE 802.1p Priority
 IEEE 802.1Q (GVRP)
 IEEE 802.1w Rapid Reconfiguration of Spanning Tree
 IEEE 802.3ab 1000BASE-T
 IEEE 802.3ad Link Aggregation (LAG)
 IEEE 802.3ae 10-Gigabit Ethernet
 IEEE 802.3af Power over Ethernet
 IEEE 802.3i 10BASE-T
 IEEE 802.3u 100BASE-X
 IEEE 802.3x Flow Control
 IEEE 802.3z 1000BASE-X
 RFC 768 UDP
 RFC 791 IP
 RFC 792 ICMP
 RFC 793 TCP
 RFC 854 TELNET
 RFC 925 Multi-LAN Address Resolution
 RFC 950 Internet Standard Subnetting Procedure
 RFC 951 BOOTP
 RFC 1027 Proxy ARP
 RFC 1058 RIPv1
 RFC 1122 Host Requirements
 RFC 1141 Incremental updating of the Internet checksum
 RFC 1213 Management Information Base for Network Management of TCP/IP-based internets
 RFC 1256 ICMP Router Discovery Protocol (IRDP)
 RFC 1305 NTPv3
 RFC 1350 TFTP Protocol (revision 2)
 RFC 1519 CIDR
 RFC 1542 BOOTP Extensions
 RFC 1723 RIP v2
 RFC 1812 IPv4 Routing
 RFC 1887 An Architecture for IPv6 Unicast Address Allocation
 RFC 2131 DHCP

RFC 3162 RADIUS and IPv6
 RFC 3306 Unicast-Prefix-based IPv6 Multicast Addresses
 RFC 3307 IPv6 Multicast Address Allocation
 RFC 3315 DHCPv6 (client and relay)
 RFC 3484 Default Address Selection for IPv6
 RFC 3493 Basic Socket Interface Extensions for IPv6
 RFC 3513 IPv6 Addressing Architecture
 RFC 3542 Advanced Sockets API for IPv6
 RFC 3587 IPv6 Global Unicast Address Format
 RFC 3596 DNS Extension for IPv6
 RFC 3810 MLDv2 for IPv6
 RFC 4113 MIB for UDP
 RFC 4443 ICMPv6

MIBs

RFC 1212 Concise MIB Definitions
 RFC 1213 MIB II
 RFC 1493 Bridge MIB
 RFC 1657 BGP-4 MIB
 RFC 1724 RIPv2 MIB
 RFC 1757 Remote Network Monitoring MIB
 RFC 1850 OSPFv2 MIB
 RFC 2012 SNMPv2 MIB for TCP
 RFC 2013 SNMPv2 MIB for UDP
 RFC 2233 Interface MIB
 RFC 2452 IPV6-TCP-MIB
 RFC 2454 IPV6-UDP-MIB
 RFC 2465 IPv6 MIB
 RFC 2466 ICMPv6 MIB
 RFC 2571 SNMP Framework MIB
 RFC 2572 SNMP-MPD MIB
 RFC 2573 SNMP-Target MIB
 RFC 2574 SNMP USM MIB
 RFC 2618 RADIUS Authentication Client MIB
 RFC 2620 RADIUS Accounting Client MIB
 RFC 2665 Ethernet-Like-MIB
 RFC 2674 Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering, and Virtual Extensions
 RFC 2737 Entity MIB (Version 2)
 RFC 2787 VRRP MIB
 RFC 2819 RMON MIB
 RFC 2925 Ping MIB
 RFC 3414 SNMP-User based-SM MIB
 RFC 3415 SNMP-View based-ACM MIB
 RFC 4113 UDP MIB

Network management

IEEE 802.1AB Link Layer Discovery Protocol

Technical Specifications

RFC 2236 IGMP Snooping
 RFC 2338 VRRP
 RFC 2375 IPv6 Multicast Address Assignments
 RFC 2616 HTTP Compatibility v1.1
 RFC 2644 Directed Broadcast Control
 RFC 2865 Remote Authentication Dial In User Service (RADIUS)
 RFC 2866 RADIUS Accounting
 RFC 3246 Expedited Forwarding PHB
 RFC 3410 Applicability Statements for SNMP
 RFC 3414 User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)
 RFC 3415 View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)
 RFC 3417 Transport Mappings for the Simple Network Management Protocol (SNMP)
 RFC 3484 Default Address Selection for Internet Protocol version 6 (IPv6)
 RFC 3493 Basic Socket Interface Extensions for IPv6
 RFC 3542 Advanced Sockets Application Program Interface (API) for IPv6
 RFC 3587 IPv6 Global Unicast Address Format
 RFC 3596 DNS Extensions to Support IP Version 6
 RFC 3623 Graceful OSPF Restart
 RFC 3704 Unicast Reverse Path Forwarding (URPF)
 RFC 3768 VRRP
 RFC 3810 Multicast Listener Discovery Version 2 (MLDv2) for IPv6
 RFC 4113 Management Information Base for the User Datagram Protocol (UDP)
 RFC 4213 Basic IPv6 Transition Mechanisms
 RFC 4443 Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification
 802.1r - GARP Proprietary Attribute Registration Protocol (GPRP)

IP multicast

RFC 2236 IGMPv2
 RFC 2710 Multicast Listener Discovery (MLD) for IPv6
 RFC 2858 Multiprotocol Extensions for BGP-4
 RFC 3376 IGMPv3
 RFC 3569 An Overview of Source-Specific Multicast (SSM)
 RFC 3618 Multicast Source Discovery Protocol

(LLDP)
 IEEE 802.1D (STP)
 RFC 1157 SNMPv1
 RFC 1212 Concise MIB definitions
 RFC 1215 SNMP Generic traps
 RFC 1757 RMON 4 groups: Stats, History, Alarms and Events
 RFC 1901 SNMPv2 Introduction
 RFC 1918 Private Internet Address Allocation
 RFC 2373 Remote Network Monitoring Management Information Base for High Capacity Networks
 RFC 2571 An Architecture for Describing SNMP Management Frameworks
 RFC 2572 Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)
 RFC 2573 SNMP Applications
 RFC 2574 SNMPv3 User-based Security Model (USM)
 RFC 2575 SNMPv3 View-based Access Control Model (VACM)
 RFC 2576 Coexistence between SNMP versions
 RFC 2578 SMIv2
 RFC 2581 TCP6
 RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)
 RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations
 RFC 3176 sFlow
 RFC 3410 Introduction to Version 3 of the Internet-standard Network Management Framework
 RFC 3414 SNMPv3 User-based Security Model (USM)
 RFC 3415 SNMPv3 View-based Access Control Model VACM)
 ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)
 SNMPv1/v2c/v3

OSPF

RFC 1587 OSPF NSSA
 RFC 1850 OSPFv2 Management Information Base (MIB), traps
 RFC 2328 OSPFv2
 RFC 2370 OSPF Opaque LSA Option
 RFC 3623 Graceful OSPF Restart

QoS/CoS

IEEE 802.1p (CoS)
 RFC 2474 DSCP DiffServ
 RFC 2475 DiffServ Architecture

Technical Specifications

(MSDP)
RFC 3973 PIM Dense Mode
RFC 4601 PIM Sparse Mode

IPv6

RFC 1881 IPv6 Address Allocation Management
RFC 1887 IPv6 Unicast Address Allocation
Architecture
RFC 1981 IPv6 Path MTU Discovery
RFC 2080 RIPng for IPv6
RFC 2373 IPv6 Addressing Architecture
RFC 2375 IPv6 Multicast Address Assignments
RFC 2460 IPv6 Specification
RFC 2461 IPv6 Neighbor Discovery
RFC 2462 IPv6 Stateless Address Auto-
configuration
RFC 2463 ICMPv6

RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)
RFC 4594 Configuration Guidelines for DiffServ
Service Classes

Security

IEEE 802.1X Port Based Network Access Control
RFC 1492 TACACS+
RFC 1918 Address Allocation for Private Internets
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
Access Control Lists (ACLs)
MAC Authentication
Port Security
SSHv2 Secure Shell

Accessories

HPE 5500 EI Switch Series accessories	Modules	
	<u>HP 5500 2-port 10GbE XFP Module</u>	JD359B
	HP 5500 2-port 10GbE Local Connect Module	JD360B
	<u>HP 5500 1-port 10GbE XFP Module</u>	JD361B
	<u>HP 5500/4800 2-port GbE SFP Module</u>	JD367A
	HP 5500/5120 2-port 10GbE SFP+ Module	JD368B
	NEW HP 5500/5120 2-port 10GBASE-T Module	JG535A
	Transceivers	
	<u>HP X125 1G SFP LC LH40 1310nm Transceiver</u>	JD061A
	<u>HP X120 1G SFP LC LH40 1550nm Transceiver</u>	JD062A
	<u>HP X125 1G SFP LC LH70 Transceiver</u>	JD063B
	HP X110 100M SFP LC LH40 Transceiver	JD090A
	HP X110 100M SFP LC LH80 Transceiver	JD091A
	HP X130 SFP+ LC SR Transceiver	JD092B
	HP X130 SFP+ LC LRM Transceiver	JD093B
	HP X130 SFP+ LC LR Transceiver	JD094B
	<u>HP X120 1G SFP LC BX 10-U Transceiver</u>	JD098B
	<u>HP X120 1G SFP LC BX 10-D Transceiver</u>	JD099B
	HP X110 100M SFP LC FX Transceiver	JD102B
	HP X130 10G XFP LC LR Transceiver	JD108B
	HP X130 10G XFP LC SR Transceiver	JD117B
	<u>HP X120 1G SFP LC SX Transceiver</u>	JD118B
	<u>HP X120 1G SFP LC LX Transceiver</u>	JD119B
	HP X110 100M SFP LC LX Transceiver	JD120B
	HP X135 10G XFP LC ER Transceiver	JD121A
	HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095C
	HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096C
	HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097C
	HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable	JG081C
	HP X240 10G SFP+ SFP+ 7m Direct Attach Copper Cable	JC784C
	<u>HP X120 1G SFP RJ45 T Transceiver</u>	JD089B
	HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
Cables		
HP X230 Local Connect 100 cm CX4 Cable	JD364B	
HP X230 Local Connect CX4 300 cm Cable	JD365A	
<u>HP 0.5 m Multimode OM3 LC/LC Optical Cable</u>	AJ833A	
<u>HP 1 m Multimode OM3 LC/LC Optical Cable</u>	AJ834A	
<u>HP 2 m Multimode OM3 LC/LC Optical Cable</u>	AJ835A	
<u>HP 5 m Multimode OM3 LC/LC Optical Cable</u>	AJ836A	
<u>HP 15 m Multimode OM3 LC/LC Optical Cable</u>	AJ837A	
<u>HP 30 m Multimode OM3 LC/LC Optical Cable</u>	AJ838A	
<u>HP 50 m Multimode OM3 LC/LC Optical Cable</u>	AJ839A	

Accessories

<u>HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable</u>	QK732A
<u>HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable</u>	QK733A
<u>HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable</u>	QK734A
<u>HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable</u>	QK735A
<u>HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable</u>	QK736A
<u>HP 50 m PremierFlex OM3+ LC/LC Optical Cable</u>	QK737A
HP X230 Local Connect 50cm CX4 Cable	JD363B
Power Supply	
HP 5800/5500 150W AC Power Supply	JD362A
HP 5800/5500 150W DC Power Supply	JD366A
HP RPS 800 Redundant Power System	JD183A
<u>HP RPS 1600 Redundant Power System</u>	JG136A
<u>HP RPS 1600 1600W AC Power Supply</u>	JG137A
Power cords	
HP X290 1000 A JD5 2m RPS Cable	JD187A
HP X290 1000 A JD5 Non-PoE 2m RPS Cable	JD188A
HP X290 1000 B JD5 2m RPS Cable	JD189A
HP X290 500/800 1m RPS Cable	JD190A
HP X290 500 U 1m RPS Cable	JD185A

Accessory Product Details

NOTE: Details are not available for all accessories. The following specifications were available at the time of publication.

HP 5500 2-port 10GbE XFP Module (JD359B)	Ports Services	2 XFP 10-GbE ports; Duplex: full only Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office
HP 5500 1-port 10GbE XFP Module (JD361B)	Ports Services	1 XFP 10-GbE port; Duplex: full only Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office
HP 5500/4800 2-port GbE SFP Module (JD367A)	Ports Services	2 SFP 1000 Mbps ports Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office
HP X125 1G SFP LC LH40 1310nm Transceiver (JD061A)	Ports Connectivity	1 LC 1000Base-LH port (no IEEE standard exists for 1550 nm optics) Connector type LC Wavelength 1310 nm
A small form-factor pluggable SFP Gigabit LH40 transceiver that provides a full duplex Gigabit solution up to 40km on a single-mode fiber.	Physical characteristics	Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	Electrical characteristics	Full configuration weight 0.04 lb. (0.02 kg) Power consumption typical 0.8 W Power consumption maximum 1.0 W
	Cabling	Cable type: Single-mode fiber optic, complying with ITU-T G.652;
		Maximum distance:
		<ul style="list-style-type: none"> 40km distance
	Services	Fiber type Single Mode Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

Accessory Product Details

HP X120 1G SFP LC LH40 Ports

1550nm Transceiver (JD062A)

A small form-factor pluggable (SFP) Gigabit LH40 transceiver that provides a full-duplex Gigabit solution up to 40 km on a single mode fiber.

		1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)	
Connectivity	Connector type	LC	
	Wavelength	1550 nm	
Physical characteristics	Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)	
	Full configuration weight	0.04 lb. (0.02 kg)	
Electrical characteristics	Power consumption typical	0.8 W	
	Power consumption maximum	1.0 W	
Cabling	Cable type:	Single-mode fiber optic, complying with ITU-T G.652;	
	Maximum distance:	<ul style="list-style-type: none"> 40km distance 	
Services	Fiber type	Single Mode	
	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office		

HP X125 1G SFP LC LH70 Ports

Transceiver (JD063B)

A small form-factor pluggable (SFP) Gigabit LH70 transceiver that provides a full-duplex Gigabit solution up to 70km on a single-mode fiber.

		1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)	
Connectivity	Connector type	LC	
	Wavelength	1550 nm	
Physical characteristics	Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)	
	Full configuration weight	0.04 lb. (0.02 kg)	
Electrical characteristics	Power consumption typical	0.8 W	
	Power consumption maximum	1.0 W	
Cabling	Cable type:	Single-mode fiber optic, complying with ITU-T G.652;	
	Maximum distance:	<ul style="list-style-type: none"> 70km 	
Services	Fiber type	Single Mode	
	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office		

HP X120 1G SFP LC BX Ports

1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-U);

Accessory Product Details

10-U Transceiver

(JD098B)

A small form-factor pluggable (SFP) Gigabit LX-BX10-U transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.

Connectivity	Duplex: full only	Connector type	LC
Physical characteristics	Dimensions		2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	Full configuration weight		0.04 lb. (0.02 kg)
Electrical characteristics	Power consumption typical		0.8 W
	Power consumption maximum		1.0 W
Cabling	Maximum distance:		
	• 10km		
	Fiber type		Single Mode
Notes	TX 1310nm RX 1490nm		
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office		

HP X120 1G SFP LC BX 10-D Transceiver

(JD099B)

A small form-factor pluggable (SFP) Gigabit LX-BX10-D transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.

Ports	1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-D); Duplex: full only		
Connectivity	Connector type		LC
Physical characteristics	Dimensions		2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	Full configuration weight		0.04 lb. (0.02 kg)
Electrical characteristics	Power consumption typical		0.8 W
	Power consumption maximum		1.0 W
Cabling	Maximum distance:		
	• Up to 10km		
	Fiber type		Single Mode
Notes	TX 1490nm RX 1310nm		
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office		

HP X120 1G SFP LC SX Transceiver (JD118B)

A small form-factor

Ports	1 LC 1000BASE-SX port		
Connectivity	Connector type		LC
	Wavelength		850 nm
Physical characteristics	Dimensions		2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17

Accessory Product Details

pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550m on a Multimode fiber.

		cm)
	Full configuration weight	0.04 lb. (0.02 kg)
Electrical characteristics	Power consumption typical	0.8 W
	Power consumption maximum	1.0 W
Cabling	Maximum distance:	
	• FDDI Grade distance = 220m	
	• OM1 = 275m	
	• OM2 = 500m	
	• OM3 = Not Specified by standard	
	Cable length	up to 550m
	Fiber type	Multi Mode
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office	

HP X120 1G SFP LC LX Transceiver (JD119B)

A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF

Ports	1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)	
Connectivity	Connector type	LC
	Wavelength	1300 nm
Physical characteristics	Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	Full configuration weight	0.04 lb. (0.02 kg)
Electrical characteristics	Power consumption typical	0.8 W
	Power consumption maximum	1.0 W
Cabling	Cable type: Either single mode or multimode;	
	Maximum distance:	
	• 550m for Multimode	
	• 10km for Singlemode	
	Fiber type	Both
Services	Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office	

HP X120 1G SFP Ports RJ45 T

1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T)

Connectivity

Connector type

RJ-45

Accessory Product Details

Transceiver (JD089B)	Physical characteristics	Dimensions	2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm)
	Electrical characteristics	Full configuration weight	0.07 lb. (0.03 kg)
A small form factor pluggable (SFP) Gigabit 1000Base-T transceiver that provides a full duplex Gigabit solution up to 100m on a Cat-5+ cable.	Cabling	Power consumption typical	0.8 W
		Power consumption maximum	1.0 W
	Services	Cable type: 1000BASE-T: Category 5 (5E or better recommended), 100 Ω differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T; Maximum distance: • 100m Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office	

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)	Cabling	Cable type: 50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m
	Notes	Maximum distance: 10Gbps Transfer Rate (Ethernet): 300m Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end. <ul style="list-style-type: none"> • Dimensions: Core diameter: 50 ± 3.0μm Cladding diameter: 125 ± 2.0μm Coating diameter: 245 ± 10μm • Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm. • Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links. • CABLE: The cable is duplex zipcord graded index 50/125μm multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows. • BULK CABLE & CABLE ASSEMBLY CONFIGURATION: • Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic. • Jacket Color: Aqua for OM3 multimode per TIA 598 • Boot Color: White • Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters. • Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46. • Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at

Accessory Product Details

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP 1 m Multimode OM3 Cabling LC/LC Optical Cable (AJ834A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP 2 m Multimode OM3 Cabling LC/LC Optical Cable (AJ835A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Accessory Product Details

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP 5 m Multimode OM3 Cabling LC/LC Optical Cable (AJ836A)

Cable type:

50/125 μm core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.

Accessory Product Details

- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP 15 m Multimode OM3 Cabling LC/LC Optical Cable

(AJ837A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 \pm 3.0um Cladding diameter: 125 \pm 2.0um Coating diameter: 245 \pm 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.

Accessory Product Details

- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP 30 m Multimode OM3 LC/LC Optical Cable (AJ838A)

Cabling

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 \pm 3.0 μm Cladding diameter: 125 \pm 2.0 μm Coating diameter: 245 \pm 10 μm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP 50 m Multimode OM3 LC/LC Optical

Cabling

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for

Accessory Product Details

Cable (AJ839A)

distances of up to 300 m;

Notes

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m

Accessory Product Details

Services

added for lengths >30m

- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable (QK733A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable (QK734A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm

Accessory Product Details

Services

@ 23°C as tested in accordance with EIA 455-45

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable (QK735A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable (QK736A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the Hewlett Packard Enterprise website at

Accessory Product Details

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable (QK737A) **Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HPE PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP RPS1600 Redundant Power System (JG136A) **Ports**

8 redundant power supply ports
Restrictions: two -56V/25A DC(PoE); six -56V/8A DC(non-PoE)

Physical characteristics	Dimensions	15.63(d) x 17.32(w) x 1.74(h) in. (39.7 x 44 x 4.42 cm)
	Weight	14.11 lb. (6.4 kg)
Environment	Full configuration weight	16.75 lb. (7.6 kg)
	Operating temperature	14°F to 122°F (-10°C to 50°C)
	Operating relative humidity	5% to 95%
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%
	Altitude	up to 13,123 ft. (4 km)
Electrical characteristics	Acoustic	Pressure: 53 dB; ISO 7779, ISO 9296
	Voltage	100-120/200-240 VAC
	Current	30/60 A

Accessory Product Details

	Idle power	38 W
	Maximum power rating	3550 W
	RPS power	3200 W
	PoE power	2800 W
	RPS	-55 V
	PoE	-55 V
	Frequency	50/60 Hz
	Notes	<p>Idle power is the actual power consumption of the device with no ports connected.</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> <p>With one RPS1600 Power Supply, the PRS1600 Redundant Power System can provide 1600W power output; With two PRS1600 Power Supplies, the output power is 3200W.</p>
Safety		CE Labeled; UL 60950-1; IEC 60950-1; ICES-003; FCC Part 15, Subpart B; EU RoHS Compliant; EN 60950-1/A11; C-Tick; VCCI Class A; ROHS Compliance; EN 300386
Services		Refer to the Hewlett Packard Enterprise website at http://www.hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HP RPS1600 1600W AC Power Supply (JG137A)	Physical characteristics	Dimensions	8.19(d) x 4.96(w) x 1.63(h) in. (20.8 x 12.6 x 4.15 cm)
		Weight	3.02 lb. (1.37 kg)
	Environment	Operating temperature	14°F to 122°F (-10°C to 50°C)
		Operating relative humidity	5% to 95%
		Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
		Nonoperating/Storage relative humidity	5% to 95%
	Electrical characteristics	Voltage	100-120/200-240 VAC
		Current	15/30 A
		Maximum power rating	1600 W
		Frequency	50/60 Hz
		Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if

Accessory Product Details

equipped), 100% traffic, all ports plugged in, and all modules populated.

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

Summary of Changes

Date	Version History	Action	Description of Change:
01-Dec-2015	From Version 33 to 34	Changed	Overview and Technical Specifications updated
01-Dec-2014	From Version 32 to 33	Changed	Warranty and support updated
03-Jul-2014	From Version 31 to 32	Changed	Configuration menu updated.
10-Jun-2014	From Version 30 to 31	Added	Added Opacity Shield Kit and Tamper Evidence Labels to Configuration.
15-Apr-2014	From Version 29 to 30	Changed	Notes section for Modules was revised in Configuration.
19-Mar-2014	From Version 28 to 29	Changed	Transceivers and Cables were revised in Configuration.
25-Feb-2014	From Version 27 to 28	Changed	HP 5500-24G-SFP EI Switch was revised in Configuration.
16-Jan-2014	From Version 26 to 27	Changed	Features and benefits was revised.
17-Dec-2013	From Version 25 to 26	Changed	Modules were revised in Configuration.
09-Dec-2013	From Version 24 to 25	Changed	Notes for Modules were revised in Configuration.
08-Nov-2013	From Version 23 to 24	Changed	Switch Chassis, Box Level Integrated CTO Models, Rack Level Integrated Models, Modules, and Cables were revised.
09-Oct-2013	From Version 22 to 23	Removed	HP X110 100M SFP LC FX Dual Mode Transceiver and HP X110 SFP LC LX10 Transceiver were removed.
30-Sep-2013	From Version 21 to 22	Changed	Configuration was revised. Features and Benefits was revised. Product overview was revised.
30-Sep-2013	From Version 21 to 22	Changed	Configuration was revised. Features and Benefits was revised. Product overview was revised.
19-Aug-2013	From Version 20 to 21	Changed	Box Level Integration CTO Models was revised in Configuration
12-Jul-2013	From Version 19 to 20	Changed	Acoustic was added to Technical Specifications Models were removed throughout
02-Jul-2013	From Version 18 to 19	Added	Added new skus in the Modules section of Configuration.
27-Jun-2013	From Version 17 to 18	Changed	Standards and protocols was revised
21-Jun-2013	From Version 16 to 17	Changed	Security in Features and Benefits was revised Standards and protocols was revised in Technical Specifications
10-Jun-2013	From Version 15 to 16	Changed	Updated the notes section for CTO Switch Chassis in Configuration.

Summary of Changes

27-May-2013	From Version 14 to 15	Changed	Updated the Configuration Information.
22-May-2013	From Version 13 to 14	Changed	Updated the Configuration Information.
20-May-2013	From Version 12 to 13	Changed	Minor corrections were made to the Configuration section.
13-May-2013	From Version 10 to 12	Added	Added the Configuration Section.
14-May-2012	From Version 9 to 10	Changed	Features and Benefits, Accessories, and the weight and dimensions for each spec were revised.
20-Apr-2012	From Version 8 to 9	Changed	Features and benefits was revised.
15-Mar-2012	From Version 7 to 8	Changed	Features and benefits and Accessories were revised.
05-Mar-2012	From Version 6 to 7	Changed	The Introduction paragraph was revised.
26-Sep-2011	From Version 3 to 6	Changed	Model descriptions and Services were revised.
30-Aug-2011	From Version 2 to 3	Changed	Added two new models and revised Accessories and Features and Benefits.
16-Mar-2011	From Version 1 to 2	Changed	Accessories were revised.

Summary of Changes



Sign up for updates

★ Rate this document



© Copyright 2015 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: www.hp.com/networking

c04111661 - 13808 - Worldwide - V34 - 1-December-2015